

## PharmaLine DO AF H


### *UV DEOZONATION FOR PURIFIED WATER DISTRIBUTION LOOPS*

Our **PharmaLine DO AF H** UV systems are designed for hygiene based on cGMP principles specifically for providing ozone destruction for pharmaceutical purified water distribution loops. When installed in a distribution loop the PharmaLine DO AF H will remove residual ozone dosed into the water to maintain microbiological integrity. The UV system can be remotely controlled to turn off to allow residual ozone to treat the purified water loop during a SIP and then be turned on again to remove the ozone before the loop is put back into service. Each system comes with a UV monitor/UV sensor to measure the lamp output making it easy to monitor and log performance. The UV systems are all single lamp design with long lamp life providing reduced operating costs.




Application  
Optimised UV for  
Pharmaceuticals

# POTENTIAL LOCATIONS OF THE PHARMALINE DO AF H™



KEY FEATURES	WHAT IT GIVES YOU	BENEFITS FOR YOU
INTELLIGENCE		
UV intensity monitor / sensor measuring UV wavelengths	Continuous verification of performance with in-built low intensity alarm	Easy to monitor and log system performance
OPTIMISATION		
Single lamp technology	Optimised for ozone reduction	Proven log reduction of ozone
	Lower power use than comparable multi-lamp systems	Lower operating costs
	Lower maintenance cost compared to multi-lamp systems	
Designed for the pharmaceutical industry based on cGMP principles	Sanitary design with <0.38 µm internal surface finish and tri-clamp connections as standard	Industry compliance; reduced risk of microbiological contamination; enhances control of your process as part of a multi-barrier system
	FDA-approved materials used for all wetted parts	
	Remote control function	Matches automated SIP ozonation procedure
INTEGRATION		
Compact design	Can be fitted to skids	Easy integration
	Can be retrofitted to existing process	



MODEL NUMBER	MAX POWER (W)	MIN T10(%)	DIMENSIONS (MM)									APPROX WEIGHT (KG)	
			A	B	C	D	E	DN	K*	L	M**	Chamber (Empty)	Control Cabinet
PharmaLine DO AF H 0001	115	60	1388	1273	82	1300	102	40	170	300	490	9	11
PharmaLine DO AF H 0002	165	60	1388	1273	82	1300	102	50	170	300	490	9	11
PharmaLine DO AF H 0005	345	60	1388	1273	82	1300	102	50	170	300	490	9	11
PharmaLine DO AF H 0008	345	60	1437	1300	150	1300	168	80	170	300	490	24	11
PharmaLine DO AF H 0020	700	60	1980	1825	200	1900	206	80	225	400	690	46	22

All dimensions are approximate for clearance purposes only. We have a policy of continuous product development, exact drawings are available on request.

All specifications are subject to change without notification. Your distributor or our account manager can advise on correct sizing and specification requirements.

\* Allow dimension L in front of cabinet for door opening and panel access.

\*\* M dimension includes the space for the cabinet mounting brackets but you need to allow space below the cabinet for cable entry and access (minimum of 250 mm).

UV CHAMBER		CABINET (CONTROLLER ELECTRON RCM)	
Material:	StSt 316L / 1.4404	Material:	Polyester coated carbon steel
Internal finish:	<0.38 µm Ra welds left as laid, electropolished and passivated	Degree of protection:	IP66 / NEMA 4 except DO AF H 0020 which is IP54 NEMA 12
External finish:	Sateen polish (120 grit) electropolished and passivated	Supply voltages (nominal):	230 V (+/- 10%) 50/60 Hz
Process (mating) connections:	Tri-clamp. For sizes see Tri-clamp technical bulletin 910425-0001	Operating temperature range:	5°C to 40°C
Drain connection:	Tri-clamp to ISO 2852	Relative humidity:	<95% non-condensing, except DO AF H 0020, which is 85%
End plate:	Removable tri-clamp	Cooling fans:	DO AF H 0020 only
Degree of protection:	IP65 equivalent to NEMA 4 but not for outside use	Interconnecting cable lengths:	5 m
Arc tube (lamp):	Low pressure amalgam	CUSTOMER OUTPUTS	
Arc tube enclosure:	Pure quartz (F200)	4-20 mA passive output:	UV intensity %
Number of arc tubes (lamps):	1	VFC outputs:	Lamp ON and Low UV warning
Expected lamp life:	12000 hours	CUSTOMER INPUTS	
Temperature sensor:	Snap stat on DO AF H 0020 only	VFC inputs:	Remote stop/start and remote reset
UV monitor:	Wet UV monitor	CUSTOMER COMMUNICATIONS PORT	
Working fluid temperature:	5°C to 40°C	None	
Maximum CIP temperature:	130°C (DO AF H 0001 - DO AF H 0005) 95°C (DO AF H 0008 - DO AF H 0020) with cabinet electrically isolated	APPROVALS	
Hydrostatically pressure tested:	Yes to PED requirements EN 13445	CE marked	
Chamber mounting:	Horizontal or vertical except DO AF H 0020 which is horizontal only		
Operating pressure:	10 bar (positive pressure only)		
Seals:	EPDM, FDA 21 CFR 177.2600, USP Class VI 121°C approved		

OPTIONS	
Document Support Pack	
Cabinet material: Stainless steel 304	
Operation and Maintenance manual and printed Installation and Commissioning manual in Chinese, English, French, German and Spanish	
Maximum CIP temperature: 130°C (DO AF H 0008 - DO AF H 0020, panel switched off)	
Welder Document Pack for chamber construction	
Skid mounting (not shipboard or earthquake zone)	



# PharmaLine DO AF H

Also available in our Pharmaceutical product range...



**PHARMALINE  
PQ+PQH**

3rd party bioassayed  
systems for critical  
treatment or as part of a  
pathogen barrier



**PHARMALINE  
D+DH**

Treatment as part of a  
multi barrier approach  
or secondary hygiene  
maintenance



**PHARMALINE  
DC**

Chlorine removal

## Canada

+1 980 256 5700  
americas@nuvonicuv.com

## China

+86 216 167 9599  
apac@nuvonicuv.com

## Germany

+44 175 351 5300  
emea@nuvonicuv.com

## Malaysia

+60 16 440 8834  
sea@nuvonicuv.com

## Mexico

+1 980 256 5700  
americas@nuvonicuv.com

## United Kingdom

+44 175 351 5300  
emea@nuvonicuv.com

## USA

+1 980 256 5700  
americas@nuvonicuv.com



# NUVONIC

A Halma company

*formerly Aquionics, Berson, Hanovia and Orca GmbH*

